



LIVEN LV Series

AGM (Absorbent Glass Material) technology with gas recombination. VRLA (Valve Regulated Lead Acid Battery). Maintenance-Free Sealed Lead Acid Battery. Battery with 5 years design life in float service. Cycle use 1: Up to 260 cycles at 100% DOD. Cycle use 2: Up to 500 cycles at 50% DOD.


Application:

- Telecommunications
- Alarm and security system
- Uninterrupted Power Supplies
- Communication power supply
- Medical equipments
- DC power supply
- Emergency backup power supply

Dimensions:

Length	151±1.5mm (5.94 inches)
Width	98±1.5mm (3.86 inches)
Height	95±1.5mm (3.74 inches)
Total Height	101±1.5mm (3.98 inches)

Drawing:



Specification:

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity	12Ah@20hour-rate to 1.75V per cell @25°C
Weight	Approx. 3.40 Kg ±2%
Internal Resistance	Approx. 16.5 mΩ
Terminal	F2
Max. Discharge Current	120A (5 sec)
Short Circuit Current	570A
Design Life	5 years (Float charging) Eurobat (20°C): 3-5 years
Recommended Maximum Charging Current	3.6 A
Standby Use Voltage	13.7 V~13.9 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -15°C~50°C Charge: -10°C~45°C Storage: -15°C~50°C
Normal Operating Temperature Range	25°C±5°C
Self Discharge	LIVEN Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.




Constant Current Discharge (CC, Unit: A) at 25°C (77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	46.15	30.41	22.66	13.11	7.654	4.516	3.283	2.614	2.207	1.475	1.201	0.625
1.65V	44.48	29.50	22.07	12.83	7.513	4.450	3.239	2.582	2.181	1.460	1.190	0.620
1.70V	42.31	28.31	21.29	12.45	7.325	4.362	3.181	2.539	2.147	1.440	1.174	0.613
1.75V	39.53	26.77	20.27	11.95	7.078	4.246	3.104	2.481	2.102	1.414	1.154	0.604
1.80V	36.01	24.81	18.96	11.30	6.755	4.093	3.003	2.405	2.043	1.379	1.127	0.592
1.85V	31.69	22.35	17.31	10.48	6.340	3.894	2.870	2.306	1.964	1.332	1.092	0.577


Constant Power Discharge (CP, Unit: W/Battery) at 25°C (77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	476.58	314.76	241.26	145.08	87.18	52.14	38.16	30.54	25.92	17.52	14.40	7.50
1.65V	471.60	313.50	239.88	144.00	86.46	51.72	37.92	30.36	25.74	17.40	14.28	7.44
1.70V	453.60	304.26	233.46	140.52	84.60	50.88	37.32	29.88	25.38	17.22	14.10	7.38
1.75V	431.34	292.86	225.54	136.26	82.14	49.74	36.60	29.34	24.96	16.92	13.86	7.26
1.80V	399.90	276.12	213.96	130.20	78.78	48.18	35.52	28.56	24.30	16.56	13.56	7.14
1.85V	358.14	253.20	198.12	121.92	74.46	46.08	34.08	27.48	23.46	16.02	13.14	6.96


Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity



Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use

