

Specifications

Nominal Voltage (V)		12	
Nominal Capacity (AH)		100	
Dimensions	Length	329 mm	12.95 inch
	Width	172 mm	6.77 inch
	Height	216 mm	8.50 inch
	Total Height	223.5 mm	8.80 inch
Approx. Weight		34.60 kgs	76.28 lbs
Standard Terminals		V8	
Case Material		ABS UL 94-HB	


Characteristics

Capacity	100 hour rate	1.10 A	110.0 Ah
	20 hour rate	5.00 A	100.0 Ah
	10 hour rate	9.80 A	98.00 Ah
	5 hour rate	15.00 A	75.00 Ah
	1 hour rate	55.00 A	55.00 Ah
Internal Resistance		4.10 mΩ	
Max. Discharge Current (5 sec)		3260 A	
Constant Voltage Charge Method	Max. Charge Current	20 A	
	Standby Use	2.23 - 2.27 V /Cell	
	Cycle Use	2.33 - 2.37 V /Cell	
Operating Temperature Range	Discharge:	-20 ~ 55 °C (-4 ~ 131°F)	
	Charge:	-10 ~ 55 °C (14 ~ 131°F)	
	Storage:	-20 ~ 55 °C (-4 ~ 131°F)	
Temperature coefficient	For standby use:	-3.0mV / °C /Cell	
	For cycle use:	-3.3mV / °C /Cell	
Self discharge 25°C (77°F)	After 3-month	94%	
	After 6-month	88%	
	After 12-month	76%	
Temperature dependency of Capacity	40 °C (104 °F)	104%	
	25 °C (77 °F)	100%	
	0 °C (32 °F)	85%	
	-20 °C (5 °F)	65%	

Capacity with Different Temperature

Temperature	-20°C	-10°C	0°C	25°C	40°C
Capacity	60%	75%	85%	100%	104%

Dimensions




LVJ 100-12




LVJ 100-12 VRLA (valve-regulated lead acid) GEL battery is designed with 12 years float life at 25°C for wide ranging applications. With superfluous electrolyte evenly distributed in a special PVC-SiO₂ separator and a patented grid design, this battery is perfect for cyclic use, and has a greater ability to withstand heat and deep discharge. Recommended for use with photovoltaic and wind power systems. LiveN is ISO9001 and UL certified for quality assurance.




Terminal Voltage (V) and Discharge Time



Battery Voltage and Charge Time for Standby Use



Cycle Service Life



Living Energy

LIVEN
BATTERY